



www.cleaninst.com  
Customer Service: CS@cleaninst.com

## PH3500 pH/ORP controller



It is suitable for accurate measurement of pH and redox potential in harsh climate and complex industrial environment.

### Introduction:

- 128\*64 dot matrix LCD display, switchable between Chinese and English, IP65 protection level, reliable operation in any climate
- Concise menu design, simple and convenient operation, graphical prompt, beautiful and clear interface
- Digital filter is adjustable, and the hardware anti-interference ability is enhanced, which makes the measurement more stable and adapts to the complex industrial environment
- Power supply 85~260VAC, DC 18~36VDC can also be customized
- RS-485 digital interface, MODBUS - RTU communication protocol, read-write duplex communication, which can realize complete remote control of the instrument
- Two measurement functions: PH measurement or ORP ( Redox ) measurement
- With antimony electrode function, it can be used in hydrofluoric acid environment

### 5 Series

Pg1 3.5 threaded cap  
5m wire /BNC  
IP68 protection grade  
120\* Φ 13mm  
Temperature optional



### 7 Series

NPT 3/4" threaded cap  
5m wire /BNC  
PP/PPS shell  
IP68 protection grade  
160\* Φ 13mm  
Temperature optional

### pH / ORP Sensor

<b>CS1528</b>	for HF containing media
<b>CS1529</b>	for Seawater & Seawater related
<b>CS1543</b>	for Strong acid/ alkali and chemical process
<b>CS1568</b>	SNEX, for Sludge, Viscous Fluids, Paint, Sugar Process
<b>CS1597</b>	Non- aqueous media(organic phase)
<b>CS1768</b>	SNEX, for high pressure pipeline
<b>CS1778</b>	SNEX, for flue gas desulfurization process
<b>CS1788</b>	SNEX, for pure Water/ Low ion concentration water
<b>CS1753</b>	for Chemical Process
<b>CS2543</b>	CS2543 ORP, for general use
<b>CS2733</b>	CS2733 ORP, for general use
<b>CS2768</b>	CS2768 ORP, for complex industrial environment

pH	Range	-2.00~16.00 pH
	Resolution	0.01 pH
	Accuracy	±0.01 pH
	Input resistance	≥1012 Ω
ORP	Range	-2000~2000 mV
	Resolution	1 mV
	Accuracy	±1 mV
Temp.	Range	-10.0~130.0 °C
	Resolution	0.1 °C
	Accuracy	±0.3 °C
	Input type	PT1000
	TEMP compensation	Automatic/Manual
Transmission current	Output type	Two 4~20 mA (Corresponding range can be set)
	Accuracy	±1%FS
	Output load	Less than 500 Ω
Relay control	Function relay	1 (Can be set as cleaning or alarm function)
	Switch relay	2 SPST relays
	Load capacity	2.5A 230VAC
Data transmission	Transmission interface	1 RS485 Isolation voltage 2500Vrms
	Protocol	MODBUS-RTU (Read and write duplex communication)
Other parameters	Power supply	85~260VAC or 18~36VDC (User can order)
	Operating temperature	0~60°C
	Working humidity	Relative humidity < 90%
	Protection level	IP65
	Installation method	Dial installation
	Dimensions	(H×W×D) 108×108×132 mm
	Hole Size	92.5×92.5 mm (Positive tolerance)





www.cleaninst.com  
Customer Service: CS@cleaninst.com

## DO3500 Dissolved oxygen controller



It is suitable for accurate measurement and control of dissolved oxygen in all kinds of weather and complex industrial environment.

### Introduction:

- 128 \* 64 dot-matrix LCD display, switchable in Chinese and English, IP65 protection level, all-weather stable operation
- simple menu design, simple and convenient operation, graphical prompt, beautiful and clear interface
- software digital filtering is adjustable, with enhanced hardware resistance to interference, making measurements more stable and adapted to complex industrial environments
- global access power supply 85~260VAC, but also customized DC model 18 to 36 VDC
- RS-485 digital interface, MODBUS-RTU communication protocol, read and write two-way communication, can achieve remote complete control of the instrument
- The is compatible with two types of electrodes, 400nA or 80nA



Replaceable  
membrane  
cap

Replaceable  
steel sand  
film head

### Dissolved oxygen sensor

CS4551	400nA Polarographic	0 - 40 ppm
CS4751	400nA Polarographic	0 - 40 ppm
CS4763	80nA Polarographic	0 - 40 ppm
CS4773	80nA Polarographic	0 - 40 ppm

Oxygen concentration	Measuring range	0.00~40.00 m g/L
DO mg/L	Resolution ratio	0.01 m g/L
	Measurement accuracy	±0.05 m g/L
	Measurement accuracy	±0.5 %
Oxygen content %	Measuring range	0.0~400.0 %
DO %	Resolution ratio	0.1 %
	Measurement accuracy	±0.5 %
	Measurement accuracy	±0.5 %
Temperature	Measuring range	-5.0~105.0 C.0
	Resolution ratio	0.1 C
	Measurement accuracy	±0.3 C
	Temperature input	NTC22K
Transfer current	Temp. compensation	Automatic / manual
	Output, type	Two roads of 4~20 mA (the corresponding range can be set)
	Current accuracy	±1% F.S
	Output loading	less-than 500Ω
Control	Functional relay	One (which can be set to the cleaning or alarm function)
	Switch relay	2 SPST relays
	Load capacity	2.5A 230VAC
Data transmission	Coffret	All-way RS485 isolation voltage is 2500Vrms
	Protocol	MODBUS-RTU (read-write two-way communication)
Other parameters	Working power supply	85~260VAC or 18~36VDC (optional before order)
	Working temperature	0~60 C
	Work humidity	Relative humidity was <90%
	Levels of protection	IP65
	Way to install	Disk installation
	Outline dimension	(H×W×D) 108×108×132 mm
Open hole size	92.592.5 mm (positive tolerance)	





www.cleaninst.com  
Customer Service: CS@cleaninst.com

## FCL3500 Residual chlorine / hypochlorite, pH controller



It is suitable for online measurement and control of disinfectant dosing in water industry, swimming pool, water park, secondary water supply and other fields. Disinfection of medical wastewater is not applicable due to complex components

### Introduction:

- 128 \* 64 dot-matrix LCD display, switchable in Chinese and English, IP65 protection level, all-weather stable operation
- simple menu design, simple and convenient operation, graphical prompt, beautiful and clear interface
- software digital filtering is adjustable, with enhanced hardware resistance to interference, making measurements more stable and adapted to complex industrial environments
- global access power supply 85~260VAC, but also customized DC model 18 to 36 V D C
- RS-485 digital interface, MODBUS-RTU communication protocol, read and write two-way communication, can achieve remote complete control of the instrument
- The residual chlorine and pH two parameters were measured simultaneously, and the compensation was calculated automatically



### Free Chlorine Sensor

CS5530 0 - 2.000 mg/L, 0 - 20.00 mg/L

### A580L Flow cell (optional accessory)



Residual chlorine	Measuring range	0.00~20.00 mg/L
hypochloric acid	Resolution ratio	0.01 mg/L
	Measurement accuracy	±0.10 mg/L
pH value	Measuring range	0.00~14.00 pH
	Resolution ratio	0.01 pH
	Measurement accuracy	±0.01 pH
	Input impedance	≥1012Ω
Temperature	Measuring range	-10.0~130.0 C
	Resolution ratio	0.1 C
	Certainty of measurement	±0.3 C
	Temperature input	PT1000
	Temp. compensation	Automatic / manual
Transfer current	Output, type	Two roads of 4~20 mA (the corresponding range can be set)
	Current accuracy	±1% F.S
	Output loading	less-than 500Ω
Control	Functional relay	One (which can be set to the cleaning or alarm function)
	Switch relay	2 SPST relays
	load capacity	2.5A 230VAC
Data transmission	Interface Circuit	All-way RS485 isolation voltage is 2500Vrms
	Protocol	MODBUS - RTU (read-write two-way communication)
Other parameters	Working power supply	85~260VAC or 18~36VDC (optional before order)
	Working temperature	0~60 C
	Work humidity	Relative humidity was <90%
	Levels of protection	IP65
	Way to install	Panel mount
	Outline dimension	(H×W×D) 108×108×132 mm
	Open hole size	92.5 * 92.5 mm (positive tolerance)







## DOZ3500 Dissolved ozone controller



It is suitable for online measurement and control of water disinfection in the fields of tap water industry, swimming pool, water park, ozone generator, container disinfection in food and beverage industry, etc. Note that the generator that produces ozone disinfection by electrolytic water is not applicable.

### Introduction:

- 128 \* 64 dot-matrix LCD display, switchable in Chinese and English, IP65 protection level, all-weather stable operation
- simple menu design, simple and convenient operation, graphical prompt, beautiful and clear interface
- software digital filtering is adjustable, with enhanced hardware resistance to interference, making measurements more stable and adapted to complex industrial environments
- global access power supply 85~260VAC, but also customized DC model 18 to 36 V D C
- RS-485 digital interface, MODBUS-RTU communication protocol, read and write two-way communication, can achieve remote complete control of the instrument



### Dissolved ozone Sensor

CS6530 0 - 2.000 mg/L, 0 - 20.00 mg/L

### A580L Flow cell (optional accessory)



Ozone	Measuring range	0.00 ~ 20.00 mg/L
	Resolution ratio	0.01 mg/L
	Measurement accuracy	±0.10 mg/L
Temperature	Measuring range	0.00 ~ 14.00 pH
	Resolution ratio	0.01 pH
	Measurement accuracy	±0.01 pH
	Input impedance	≥ 1012Ω
	Measuring range	-10.0 ~ 130.0 C
	Resolution ratio	0.1 C
	Certainty of measurement	±0.3 C
	Temperature input	PT1000
	Temp. compensation	Automatic / manual
Transfer current	Output, type	Two roads of 4~20 mA (the corresponding range can be set)
	Current accuracy	± 1% F.S
	Output loading	less than 500Ω
Control	Functional relay	One (which can be set to the cleaning or alarm function)
	Switch relay	2 SPST relays
	load capacity	2.5A 230VAC
Data transmission	Interface Circuit	All-way RS485 isolation voltage is 2500Vrms
	Protocol	MODBUS - RTU (read-write two-way communication)
Other parameters	Working power supply	85~260VAC or 18~36VDC (optional before order)
	Working temperature	0 ~ 60 C
	Work humidity	Relative humidity was < 90%
	Levels of protection	IP65
	Way to install	Panel mount
	Outline dimension	(H×W×D) 108×108×132 mm
	Open hole size	92.5 * 92.5 mm (positive tolerance)

